



WESLEY

International

ENGINEERED-TO-ORDER MATERIAL HANDLING SOLUTIONS



Model CC 600

Standard Features

- Dual Front Wheels
- Programmable Characteristics
- Sealed 350 Amp Controller
- Tamper-proof Speed Control
- Regenerative Braking
- Electronic Throttle Control
- On-board Diagnostics
- Maintenance Management System
- Contactor-less Drive System
- Sealed Direct Drive Transaxle
- Sealed On-board Automatic Charger
- Battery Discharge Indicator
- LCD Hour Meter
- Genuine 14 Gauge Diamond Plate Steel Chassis
- Parking Brake

We build custom vehicles, too!

WESLEY INTERNATIONAL

3680 Chestnut Street
Scottsdale, GA 30079
Toll Free (866) 370.7258
Phone (404) 292-7441
Fax (404) 292-8469
www.wesleypackmule.com

PACK MULE CARGO CARRIER CC 600 SERIES

Industrial environments demand a special kind of equipment. That's why Wesley International's electric vehicles are meticulously engineered for safety, reliability and low maintenance. From the dual front wheels to the sealed motor, Wesley's vehicles offer increased stability and reduced down time. As a result, our Pack Mule™ has been the choice of discerning buyers for years. They know that increased productivity and reduced maintenance costs deliver greater profit.

Our Pack Mule CC 600 series can tow up to 2,000 lbs. These vehicles are perfect for manufacturing facilities, airports, warehouses, parts distribution centers, greenhouses and more. If our standard size doesn't fit your needs, we will custom build a vehicle that is just right for you. Our custom equipment is made with the same commitment to quality, safety and reliability.

Why buy a Pack Mule? Unique safety features, increased productivity, reduced maintenance and custom design...Can you afford not to buy a Pack Mule?

Vehicles shown
with optional
headlight



MODEL CC 620



MODEL CC 625

PACK MULE CARGO CARRIER CC 600 SERIES

SPECIFICATIONS	CC 600	CC 620	CC 625
Maximum Personnel / Position	1 / Seated	2 / Seated	1 / Standing
DIMENSIONS			
Length	105 in. (266.7 cm)	105 in. (266.7 cm)	105 in. (266.7 cm)
Width	36 in. (91.4cm)	36 in. (91.4cm)	36 in. (91.4cm)
Height	43 in. (109.2 cm)	43 in. (109.2 cm)	43 in. (109.2 cm)
Wheel Base	71 in. (180.4 cm)	71 in. (180.4 cm)	71 in. (180.4 cm)
Ground Clearance	3 in. (7.6 cm)	3 in. (7.6 cm)	3 in. (7.6 cm)
Deck Height	22.5 in. (57.2 cm)	22.5 in. (57.2 cm)	22.5 in. (57.2 cm)
Deck Size	35.5 in. (90.2 cm) x 48 in. (121.9 cm)	35.5 in. (90.2 cm) x 48 in. (121.9 cm)	35.5 in. (90.2 cm) x 48 in. (121.9 cm)
Turning Radius	110 in. (279.4 cm)	110 in. (279.4 cm)	110 in. (279.4 cm)
CAPACITIES*			
Load Capacity	1000 lb. (453.6 kg)	1000 lb. (453.6 kg)	1000 lb. (453.6 kg)
Towing Capacity	2000 lb. (907 kg)	2000 lb. (907 kg)	2000 lb. (907 kg)
WHEELS & TIRES			
Wheels	4	4	4
Tires Pneumatic	4.80 x 8 LR B	4.80 x 8 LR B	4.80 x 8 LR B
ELECTRICAL			
Battery Type	220 amp hour	220 amp hour	220 amp hour
System Voltage (Battery Quantity)	24 volt (4-6 volt) 36 volt (6-6 volt) 48 volt (6-8 volt)	24 volt (4-6 volt) 36 volt (6-6 volt) 48 volt (6-8 volt)	24 volt (4-6 volt) 36 volt (6-6 volt) 48 volt (6-8 volt)
Sealed Motor (separately excited)	5 hp / 7.5 hp / 10 hp	5 hp / 7.5 hp / 10 hp	5 hp / 7.5 hp / 10 hp
Sealed Programmable Controller	350 amp	350 amp	350 amp
Automatic Built-in Charger	25 amp, 115 volt, 60 hz	25 amp, 115 volt, 60 hz	25 amp, 115 volt, 60 hz
Instrumentation	LED Battery Discharge LCD Hour Meter	LED Battery Discharge LCD Hour Meter	LED Battery Discharge LCD Hour Meter
Removable Key Switch	3-Position Safety Key	3-Position Safety Key	3-Position Safety Key
Horn	Push Button on Console	Push Button on Console	Push Button on Console
TRANSAXLE & TRANSMISSION			
Sealed Drive Axle	Heavy-duty Direct Drive Helical Gear	Heavy-duty Direct Drive Helical Gear	Heavy-duty Direct Drive Helical Gear
Transmission Ratio	12.44:1	12.44:1	12.44:1
Programmable Maximum Speed	8 mph 11 mph 14 mph	8 mph 11 mph 14 mph	8 mph 11 mph 14 mph
STEERING, BRAKES & SUSPENSION			
Steering	3-Spoke Contour Wheel		
Service Brakes	Self-adjusting Wheel Drum Brakes		
Electronic Brakes	Programmable Electronic Regenerative Braking		
Park Brake	Foot-operated Parking Brake		

Optional Equipment

- Perma-Key Switch
- Removable Battery System
- Battery Cart with Charger
- 245 Amp Hour Batteries
- Ergonomic Anti-Fatigue Mat
- Diagnostic Handset
- Extended Deck Lengths
- Headlight / Taillight
- Back-up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Rubber Deck Cover
- Small / Large Clipboard
- Foam-filled Tires
- Non-marking Tires
- Dura Solid Tires
- Galvanized Frame
- Various Hitches

Specifications subject to change
without notice.

Wesley International electric vehicles
are designed to conform with ANSI
B56.8 and OSHA standards.

* Not to be combined. Can carry load or tow.

DISTRIBUTED BY: